



Stokbord Useful Info

- Stokbord is made from 100% re-cycled LDPE such as Back of Store Packaging and Agricultural Farm Film Waste.
- Stokbord comes as standard with an embossed finish both sides and in black
- Stokbord can have laminated colour films, logos and printed text on subject to MOQ.
- Stokbord will expand in warmer temperatures and retract in cooler temperatures but this is easily overcome by following a few simple rules.
- Boards can expand up to 1mm for every 4 degrees of temperature rise.
- Material should be fixed at an ambient temperature of approx 15 degrees.
- To allow for slight movement once the board has been fixed, make the holes in the board 2mm larger than the screws.
- Use round-headed screws or a washer and bolt. Don't use countersunk screws.
- We advise not to glue Stokbord but developments in technology mean there are adhesives on the market that can glue Stokbord but customers must make the decision on whether the adhesive works long term.
- Stokbord has a CLASS 3 fire rating
- Stokbord embossed finish means it does not scratch easily
- Ideally Stokbord should be fixed onto batons on the wall spaced 2-4ft apart. However, you can screw directly to the wall but most people attach to batons or cheap plywood.
- Stokbord can be welded but you must use a LDPE weld rod.
- Stokbord can be pressure washed; it is Chew Resistant and is Non- Toxic.
- Stokbord is ideal for cladding walls of horseboxes as it won't dent when horse kicks and won't cause any harm to the animal.
- Stokbord won't become brittle when exposed to sunlight, it absorbs UV Rays
- Stokbord can act as an insulator
- Stokbord won't fade when exposed to sunlight but may naturally fade over long periods of time such as 20-25 years.
- Stokbord is reasonably flexible and can be made into other shapes, however it is not sold as a vac-forming sheet.
- Stokbord can be bent, cut, punched, routed, welded and shaped to practically any specification.

Summary

Stokbord is a very versatile product which can be used in a variety of applications. As standard we stock 2440x1220 sheet size in 6, 9 and 12mm.

However we can make anything from 2-25mm in thickness and any sheet size up to 3660mm long and 1525mm wide. (Subject to minimum run quantity)

Typical uses include Skateboard Ramps, Ground Protection Mats, Animal Housing, Horseboxes, Trailers, Stables, Pig Pens, Cladding, Chemical Tankers this list is endless...

The following information is for guidance only and Centriforce cannot be held responsible for any inaccurate information. The customer is solely responsible for making sure that Stokbord is fit for purpose